

ITEM	QTY	PART NUMBER	DESCRIPTION
31	1	600-033-H	guard assembly
30	3	M6 x 16	Hexagon Socket Head Cap Screw
29	1	hand wheel	150mm (6") dia. bored 20mm
28	1	600-126-A	dovetail slide assembly
27	1	600-028-005-A	dovetail support - fixed
26	1	600-028-002-A	dovetail support - adjustable
25	1	600-028-004-A	lead screw
24	1	600-028-003-A	acme nut
23	1	bearing 51204	thrust bearing
22	1	600-028-001-A	load spreader bar
21	1	600-025-003-A	dovetail guide - adjustable
20	2	M8 x 25	Hexagon Socket Set Screw
19	4	M4 - 140 HV	Washer
18	4	M4 x 20 - 4.8 - Z	Recessed Pan Head Screw
17	1	600-007-001-D	nudge plate
16	1	600-007-002-C	barrier guard bracket
15	4	M4	Hex Nut
14	8	M10	Hex Nut
13	2	M5 x 12	Hexagon Socket Head Cap Screw
12	4	M12 - 140 HV	Washer
11	2	M10 x 30	Hexagon Socket Head Cap Screw
10	4	M12 x 40	Hexagon Socket Head Cap Screw
9	8	M10 x 35	Hexagon Socket Head Cap Screw
8	16	M10 - 140 HV	Washer
7	3	M8 - 140 HV	Washer
6	1	ratchet handle-M8	M8 ratchet/index handle
5	1	saw blade	saw blade, 450mm dia, 35 bore
4	1	motor assembly	CEG 4KW-2P-80F braked motor
3	1	600-116-A	Z height base plate assembly
2	1	M10x50	Hexagon Socket Head Cap Screw
1	1	saw wiring loom	See separate wiring diagram.

Parts List

Description:

File name: USA-Apollo Saw Head assembly 1 of 1

Part No.: USA-Apollo Saw Head assembly

Material:

Finish: NTS

Drawn: Nick Porter Date: 5/06/2007

This drawing and design is the property of:

**Mango Tech**


It may not be copied nor disclosed to a third party without written permission. It must be returned on request.

Tolerance unless stated otherwise

No decimal place =  $\pm 1\text{mm}$

One decimal place =  $\pm 0.2\text{mm}$

Two decimal places =  $\pm 0.05\text{mm}$



Dimensions in mm.

A3

